


Model No. / Description	Spec.	Remark	Nettó ár	Bruttó ár
<b>MAC200</b> <b>Motion Activated Camera</b> 	1. Sensor: 1.3 Mega Pixel CMOS 2. Capture Mode: Motion Activated (PIR); Time Lapse; Hybrid (Time Lapse + Motion Activated) 3. Video Resolution:1280x 720(HD Resolution, AVI) 4. Field of View: 90° 5. Motion Sensor:Detect Angle: 98°;Detect Distance:4 M 6. Capture Time: One activated capture photos for 10 seconds 7. Time Interval: Captures 10~30 frames in 10 seconds (capture rate may reduce its frames while media capacity reduced) 8. Memory Storage: Up to 32GB SDHC card 9. Power Source: Battery: 2 C Batteries; DC In: 5V 10. Battery Life: Approximately 8 months (battery life will fluctuate depending on motion activity) 11. Size (DxWxH): 100 x 100 x 57 mm 12. Weight : 300 g (without batteries and accessories) 13. Waterproof: IPx4 (safe for outdoor use) 14. OS Requirements: Microsoft Windows 98/ XP/ Vista/ Win 7	<b>Package Contents:</b> <b>1. User Manual 2. Rubber Strap x 1 3. Tree Strap x 1 4. Wall Mount (AWM100) x 1 5. NOT included 2x D cell Batteries &amp; SD card.</b>	<b>65 273 Ft</b>	<b>82 897 Ft</b>
<b>Optional Accessories for MAC200</b>				
<b>APL200</b> <b>Motion Activated Infra-RED Illuminator</b> 	1. Sensor: Dark Brown 2. Product Size : (L)100 x (W) 100 x (H) 165mm 3. Product Weight: 303 g 4. IR Wavelength: 850nm 5. Power supply: 4XD Batteries (6V, approx. 19,080 triggers) 6. LED Power 2.5W (1.25W x 2) 7. Sensor Mode: Motion Sensor & Light Sensor 8. Motion Sensor Angle: 120° 9. Motion Sensor Range: 3m 10. Delay Time: 10S 11. Operating Temperature: -5°~40°C 12. Operating Humidity: 5%~93% 13. Waterproof: IP44 14. Batter Life: about 1 year (40 triggers per day) 15. CE, RoHS Approval"	<b>Package Contents:</b> <b>1. User Manual 2. Motion Activated Infra-RED Illuminator 3. NO 4x D cell Batteries included</b>	<b>27 038 Ft</b>	<b>34 338 Ft</b>
<b>PeepHole Viewer</b>				
<b>PHV1325</b> <b>Peephole Viewer</b> 	1. Sensor: 1.3 Mega Pixel CMOS 2. PeepHole: View Angle 190 degrees (For best results please use the peephole included) 3. LCD Screen: 2.5" TFT 4. Power Source: 2 AA Batteries (good for approx. 1500 "peeps") 5. Size (LxWxH) mm: 146 (W)x 90(H) x 30(D) 6. Weight: 0.4lbs 7. 2 models for perfect images with any standard door thickness: * Model: PHV 132512 -12 mm barrel -fits any door 35~57 mm (1.38" ~ 2.24") thick. * Model: PHV 132514 -14 mm barrel -fits any door 40~69 mm (1.57" ~ 2.72") thick	<b>Base Flange, Tightening Tool, PeepHole, User Manual, 2 AA Batteries included</b>	<b>21 576 Ft</b>	<b>27 401 Ft</b>
<b>PHV-MAC</b> <b>Motion Activated PeepHole Camera</b> 	1. Sensor: 1.3 Mega Pixel CMOS 2. Built in Motion Sensor 3. PeepHole: View Angle 190 degrees (For best results please use the peephole included) 4. LCD Screen: 3.0" TFT 5. Power Source: 4 AA Batteries (good for approx. TBA") 6. Micro SD slot 7. Size (LxWxH) mm: TBA 8. Weight:TBA 9. 2 models for perfect images with any standard door thickness: * Model: PHV-MAC with 12 mm barrel -fits any door 35~37 mm (1.38" ~ 2.24") thick. * Model: PHV-MAC with 14 mm barrel -fits any door 40~69 mm (1.57" ~ 2.72") thick	<b>Base Flange, Tightening Tool, PeepHole, User Manual, 4 AA Batteries included</b>	<b>37 962 Ft</b>	<b>48 212 Ft</b>
<b>Optional Accessories for PHVMAC</b>				

<p><b>ATH100</b> Weather Resistant Housing for TLC200</p> 	<p>1. Weather Resistant Housing for TLC200  2. Dimension: 125X89X54mm  3. Material:  Main body: PC  - Outer of Diameter of the Front Lens part : acrylic  - Key &amp; side lock: Rubber  4. Weight: 110g  5. Water resistance: IP54</p>	<p><b>Weather Resistant Housing</b></p>	<p><b>12 290 Ft</b></p>	<p><b>15 608 Ft</b></p>
---	---	---	-------------------------	-------------------------